

# 22KW DOUBLE-OUTPUT EV CHARGER

The AC EV charger is a new product launched by Fox ESS . Its appearance of this product adopts a streamlined and simple design, which is more refined and glitzy. Through the App, car owners can choose the Bluetooth smart lock, timing charging function, or change it to plug and play mode. At the same time, it can monitor charging information, set EV charger parameters, bind equipment and authorization, and upgrade remote software.

**Dual output design**  
**Space saving, dual charging**



### Innovativeness Design

Streamline design



### Intelligent Control

Wireless communication (WiFi/Bluetooth)  
 OCPP communication protocol with the backend  
 Smart charge or scheduled charge by App



### Energy Saving

Standby power consumption is less than 2W, excellent energy-saving efficiency



### Flexible Option

Type 1 or Type 2 charging cable  
 App operation or plug and play  
 Wall-mounted or floor-stand installation



### Secure and Safe

6mA DC residual current protection  
 Anti-welding protection  
 IP55 rated

- Power: 22kW or 11kW\*2
- Output Current: Max.32A or 16A\*2
- Output Voltage: 400V AC
- Type 2 cable charging connector
- Compliant with OCPP 1.6 (JSON)/2.0
- App operation or RFID authentication or plug, play & 4G
- Protection Grade: IP55
- -30 ~ 50°C wide Operating Temperature
- Warranty time: 3 years



For more about the Fox ESS EV charger  
 Please visit:

[WWW.FOX-ESS.COM](http://WWW.FOX-ESS.COM)



# 22KW DOUBLE-OUTPUT EV CHARGER

## TECHNICAL SPECIFICATIONS



MODEL	AT022-DP	AT022-DS
TYPE	CHARGING PLUG	CHARGING SOCKET
<b>INPUT</b>		
Wiring Scheme	3P+N+PE	
Voltage	400Vac, ±20%	
Maximum Current	32A	
Frequency	50/60Hz	
<b>OUTPUT</b>		
Voltage	400Vac, ±20%	
Maximum Current	32A or 16A	
Rated Power	22kW or 11kW*2	
<b>USER INTERFACE &amp; CONTROL</b>		
Connector Type	Type 2 cable	Type 2 socket
RFID Reader	Mifare ISO/IEC 14443 A	
Start Mode	Plug&Play/RFID card/App	
<b>COMMUNICATION</b>		
WiFi, Bluetooth	Yes	
4G, Ethernet	Optional	
OCPP	OCPP 1.6 JSON, OCPP 2.0 optional	
<b>ENVIRONMENT</b>		
Installation	Wall-mount / Post-mount	
Operating Temperature	-30°C ~ 50°C	
Operating Humidity	5% ~ 95% No condensation	
Operating Altitude	≤2000m	
<b>DIMENSION AND WEIGHT</b>		
Product Dimension	500*350*155 mm	
Product Weight	18kg	14kg
<b>SAFETY</b>		
IP protection rating	IP55	
IK protection rating	IK08	
Residual Current Detection	AC 30mA/DC 6mA	
Electrical Protection	Over current protection, Residual current protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection	
EMC	Class B	
Certification	CE	
Certification Standard	EN/IEC 61851-1: 2019, EN/IEC 61851-21-2: 2021	